

# 4K/H.265 Mini NVR 1000 Series



MS-N1009-UT



Ultra HD



Dual Stream



Quiet  
Operation



Exquisite  
Appearance



Low  
Consumption



Mobile  
Connection





H.265  
HEVC

## KEY FEATURES

- Noise-free and energy-saving intelligent fan
- Easy to install
- Friendly GUI for configuration
- High profile H.265/H.264 coding and decoding
- Full support 2\*HDD(2.5'') max, 2TB each
- Support up to 9 IP Cameras
- DDNS for remote connection
- Multiple-level users
- Dual stream
- Ultra high definition 3840\*2160 resolution
- Size: 80mm(W)X80mm(D)X120mm(H)

## DIMENSIONS (mm)





Model		MS-N1009-UT
Video/Audio Input	Network Video Input	9-ch
	Max Stream	45Mbps
Video/Audio Output	HDMI Output	1-ch, Resolution: 3840x2160/30Hz, 1920x1080/60Hz, 1920x1080/50Hz, 1280x720/60Hz HDMI Supports Audio Output
	Dual Stream	Support
	Synchronous Preview/Playback	1*(30fps @8MP), 1*(8fps @5MP), 1*(20fps @3MP), 4*(30fps @1080P), 9*(30fps @720P)
	Recording Resolution	8MP(UHD-2160P)/6MP/5MP/4MP/3MP/1080P/UXGA/720P/VGA/D1/CIF/QCIF
Video/Audio Compression	video Compression	H.265(HEVC)/H.264
	Audio Compression	G.711 U-Law
	Sample Rate	8KHz/16KHz
	Synchronous Recording	9*5MP
Storage	Driver	2*SATA HDD(2.5")
	Capacity	Up to 2TB capacity for each HDD
Recording Management	Recording	Manual Recording, Timing Recording, Motion Detection Recording, Alarm Recording, Motion Detection or Alarm Recording, Motion Detection and Alarm Recording
	Snapshot	Manual Snapshot
	Playback	Video Playback, Image Playback
	Backup	Video Backup, Image Backup
Network	Protocol	IPv4, HTTP, NTP, SMTP, PPPoE, DDNS
External Interface	Network Interface	1*RJ45 100M/1000M
	USB Interface	2*USB 2.0
General	Power Supply	DC 12V 1.5A
	Consumption	≤6W(Without HDD)
	Working Conditions	Temperature:-10℃~+55℃ Humidity:10%~90%
	Dimensions	80mm(W)×80mm(D)×120mm(H)
	Weight	0.86Kg
	Warranty	2 Years

V3.06

